

(12) **EUROPEAN PATENT APPLICATION**


(43) Date of publication: **28.01.2004 Bulletin 2004/05**
(51) Int Cl.⁷: **H04N 7/24, G11B 27/00, G11B 15/18, G11B 27/10**
(21) Application number: **02016412.5**
(22) Date of filing: **22.07.2002**

<p>(84) Designated Contracting States: AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR Designated Extension States: AL LT LV MK RO SI</p> <p>(71) Applicant: DEUTSCHE THOMSON-BRANDT GMBH 78048 Villingen-Schwenningen (DE)</p> <p>(72) Inventors: • Schiller, Harald 30539 Hannover (DE)</p>	<ul style="list-style-type: none"> • Ostermann, Ralf 30167 Hannover (DE) • Blawat, Meinolf 30161 Hannover (DE) • Herpel, Carsten 30171 Hannover (DE) • Schewzow, Andrej 30165 Hannover (DE) <p>(74) Representative: Rittner, Karsten, Dr. Deutsche Thomson-Brandt GmbH, Karl-Wiechert-Allee 74 30625 Hannover (DE)</p>
---	---

(54) **Method and apparatus for storing and transmitting audio-visual data**

(57) Within a compressed audio-visual bit stream compression parameter sets are transmitted or stored prior to any other data referencing or using them. A special positioning is proposed for those compression parameter sets needed in cases of trick play. Embodiments are given for an extended DVD video compression scheme, where compression parameter sets of global and local nature have to be maintained in a framework of established processing units like "Cells" or "Video object units".

AV stream with in-band parameter sets (PS)



Independently Accessible Data Unit (IADU) Figure 2

EP 1 385 337 A1

Description

[0001] The invention relates to a method and to an apparatus for storing and transmitting audio-visual data.

Background

[0002] In the field of compressing audio-visual (AV) data the technological trend goes towards increasingly parameter-oriented descriptions. Seen from an encoding point of view, compression parameters in general specify, in which of several possible modes certain parts of the encoder input (AV data) shall be processed. Correspondingly, from a decoding point of view, those same compression parameters indicate, according to which of several allowable rules a section of a given compressed bit stream shall be converted back into a piece of AV data. Compression parameters can be of different nature; assuming a compression scheme where pictures are subdivided into slices, they may be "global parameters (GP)", "picture layer parameters (PLP)" and "slice layer parameters (SLP)". It is expected that GP are mostly constant, since they express parameters such as picture size or color space. However, they could be changed at the start of a random access unit, such as a GOP. Therefore, a small set of different GP sets will be referenced from within an AV bit stream. PLPs express parameters that might change more frequently, at a maximum on a per-picture basis. Hence, each coded picture will reference one out of a potentially larger set of such PLPs. Similarly, different SLPs could be referenced by each coded slice within a coded picture. It is expected that GP are mostly predetermined by the nature of the specific AV material being compressed, whereas PLP and SLP can be freely chosen as part of the encoder optimization. For the latter, the selection is likely to be based on some kind of compression efficiency measure quantifying either the coding error or the compression bit rate or both. The above-mentioned technology will be used in the developing MPEG-4 Part 10, also known as H.26L or JVT codec.

Invention

[0003] The invention is based on the recognition of the following facts.

[0004] In addition to specifying and appropriately selecting the compression parameters, they themselves must in most cases be transmitted or stored along with the AV data proper, in order to allow a meaningful decoding. This task needs to be tackled separately for each application domain, wherein the transmission or storage of compression parameters has to fulfil several, partly conflicting requirements.

• Compactness:

On a global as well as local level, compression

parameter description must be kept compact, such that the total bandwidth needed for AV plus parameters does not outweigh any gain in compression efficiency achieved by a parameterized approach. This includes a strong motivation to avoid any unnecessary repetition or other redundancy present in the compression parameters.

Consequently, the indexing mechanism from a coded picture or slice to the parameter set(s) will bound the number of parameter sets of each type that can be addressed, in order to reach the compactness goal. Hence, it must be specified whether it is possible that two different parameter sets are identified by the same (numeric or other) label. In other words, a name scope for the labels of parameter sets needs to be established.

• Decodability:

With AV data, especially on a storage medium, being prone to be accessed in non-sequential, random ways, any parameter set allocation scheme must ensure that all required compression parameters are made available when entering and decoding a bit stream at any of its entry points. This includes the important cases of any kind of trick play, and may entail allowing certain controlled forms of data redundancy.

• Compatibility:

When designing an extension of an existing specification, such as DVD for optical storage, it is desirable to maintain as many as possible of the well-understood and established system concepts. Solutions taking this into account are likely to be judged favorably in the standardization process.

[0005] Therefore, a problem to be solved by the invention is to store/transmit compression parameter sets such that those sets needed for decoding at an entry point are instantaneously available, hence optimizing for decodability without sacrificing too much bit rate.

[0006] This problem is solved by the method disclosed in claim 1. An apparatus that utilizes this method is disclosed in claim 6. A corresponding decoding method and apparatus is claimed in claim 7 and 8, respectively.

[0007] According to the inventive method a number of coding parameter sets being referenced from within the coded data of a picture or of a part of a picture are used. A first group of coding parameter sets that are being referenced within the first picture of a group of independently accessible coded pictures are inserted before the coded data of said first picture. A second group of said

coding parameter sets that are being referenced in subsequent coded pictures of said group of independently accessible coded pictures are inserted after the coded data of said first picture.

[0008] Advantageously, the second group of said coding parameters sets is placed immediately after the coded data of said first picture.

[0009] Advantageously, each coding parameter set of said second group of coding parameter sets is individually placed within said group of independently accessible coded pictures before the coded data of that picture where said coding parameter set is first being referenced.

[0010] Furthermore, it is of advantage that the numeric or other labels of each said coding parameter set need only be unique within each of said groups of independently accessible coded pictures.

[0011] According to a further advantageous embodiment both the coded data of pictures or parts of pictures as well as the coding parameter sets are conveyed in data packets for placement in an underlying storage or transmission format or protocol.

[0012] Further advantageous embodiments of the invention result from the following description.

Drawing

[0013] Exemplary embodiments of the invention are described with reference to the accompanying drawings, which show in:

- Fig.1 an AV stream with separate parameter sets;
- Fig.2. an AV stream with in-band parameter sets;
- Fig.3. an AV stream with in-band parameter sets, only included before their first reference.

Exemplary embodiments

[0014] The initially separate parameter sets shown in Figure 1 are reinserted into the main AV bit stream. This eliminates the name scope problem for parameter set labels and allows for easy random access into the AV bit stream without the need to read any auxiliary data from elsewhere on the medium. An audiovisual data format on a storage medium as well as in a broadcast transmission system will usually exhibit individually accessible data units (IADU), that permit the playback to be started at multiple locations within the AV bit stream. In the realm of MPEG video compression, IADU corresponds to the concept of "Group of Pictures" (GOP), in DVD to "Cell" or "Video Object Unit" (VOBU). Each IADU commonly starts with an entry picture (intra-coded frame) that is decodable independent from any other data in the AV bit stream, with the exception of the reference to the needed parameter sets, possibly one reference each to a GP, PLP and SLP for each coded slice within the picture.

[0015] All those parameter sets (and only those) that

are being referenced within the entry picture right before the coded data of that same entry picture are reinserted as depicted in Figure 2 or, alternatively, in a systems-level container (e.g. NAV PACK in DVD) that precedes the entry picture. The reinserted parameter sets can now be referenced by their label from any picture within the IADU. The name scope of the label is limited to the IADU. Other pictures after the entry picture may reference other PLP or SLP sets that have not yet been conveyed.

[0016] These PLP and SLP sets are conveyed right after the coded data of the entry picture. This has the advantage that those parameter sets need not to be read in trick mode, when only the entry picture of each IADU is needed. Furthermore, to ease the adaptation of AV data where parameter sets are generated on the fly as needed during encoding, an option created on the fly as needed during encoding, an option may be foreseen, to insert each parameter set at any valid location preceding the point in the bit stream where it is first being referenced as depicted in Figure 3.

[0017] One specific embodiment of the present invention, assuming carriage of MPEG-4 Part 10 video content over MPEG-2 Systems transport, requires a normative statement (through an amendment) in the MPEG-2 Systems spec (IS 13818-1:2000) to the extent that, within a PES stream, any network abstraction layer (NAL) units carrying a parameter set with a specific numeric label (parameter_set_id) shall precede any NAL units conveying coded video data which either directly reference said specific parameter set or for the decoding of which said specific parameter set is necessary. Furthermore, a normative statement is required that such parameter set NAL units shall be retained by the decoder for further reference within the name scope of the parameter_set_ids. Finally, the definition of the name scope for parameter_set_ids should not be done within MPEG-2 Systems, but explicitly be delegated to application specifications, such as an extension to the DVD spec.

[0018] As an embodiment of the present invention on the DVD side, a future extension of DVD encompassing parameterized video compression might be based on the following normative statements: That the scope of parameter_set_ids of Global Parameters (GPs) corresponds to a Cell, and that therefore video data in the first video packet in a Cell shall start with NAL units containing all GPs being referenced within that Cell, followed by video data for the VOBUs of the Cell; and that these GPs shall be retained in the decoder until the end of the Cell playback. Further, that the scope of parameter_set_ids of PLPs and SLPs corresponds to a VOB, and that therefore video data for each VOB shall start with NAL units containing all PLPs and SLPs being referenced within the first reference picture of the VOB; that subsequent NAL units might also contain further PLPs and SLPs, using different parameter_set_ids, if they are being referenced in sub-

sequent pictures of the VOB; and that any such PLPs and SLPs shall be retained in the decoder until the end of the VOB playback.

[0019] An advantage of the invention is that placing the entry picture parameter sets between the entry point and the subsequent entry picture data optimizes access speed and data availability. Placing the other needed parameter sets after the coded data of the entry picture avoids having to read such data in trick modes where they are not needed.

[0020] The necessity to repeat all used parameter sets for each IADU slightly increases the bit rate of the overall stream, however, since each used parameter set occurs only once in the bit stream, this solution is still superior to classical repetition of coding parameters on a picture or slice basis.

[0021] The invention is especially useful for transport or storage of AV bit streams. However, the invention is also applicable to other kinds of bit streams.

Claims

1. Video coding method using a number of coding parameter sets being referenced from within the coded data of a picture or of a part of a picture, wherein a first group of coding parameter sets that are being referenced within the first picture of a group of independently accessible coded pictures are inserted before the coded data of said first picture while a second group of said coding parameter sets that are being referenced in subsequent coded pictures of said group of independently accessible coded pictures are inserted after the coded data of said first picture.
2. Video coding method according to claim 1, wherein the second group of said coding parameters sets is placed immediately after the coded data of said first picture.
3. Video coding method according to claim 1, wherein each coding parameter set of said second group of coding parameter sets is individually placed within said group of independently accessible coded pictures before the coded data of that picture where said coding parameter set is first being referenced.
4. Video coding method according to any of claims 1 to 3, wherein the numeric or other labels of each said coding parameter set need only be unique within each of said groups of independently accessible coded pictures.
5. Video coding method according to any of claims 1 to 3, wherein both the coded data of pictures or parts of pictures as well as the coding parameter sets are conveyed in data packets for placement in

an underlying storage or transmission format or protocol.

6. Video coding apparatus using a method according to any of claims 1 to 5.
7. Video decoding method for decoding a video signal coded according to any of claims 1 to 5.
8. Video decoding apparatus using a method according to claim 7.

AV stream with separate parameter sets






Figure 1

AV stream with in-band parameter sets (PS)



Independently Accessible Data Unit (IADU)

7





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 01 6412

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCL.7)
X	US 5 535 008 A (MIYAZAKI KEN ET AL) 9 July 1996 (1996-07-09) * column 6, line 13-25 * * column 3, line 42-51 * * column 3, line 64-67 * ---	1-8	H04N7/24 G11B27/00 G11B15/18 G11B27/10
A	US 6 118 927 A (ARAFUNE TAKEO ET AL) 12 September 2000 (2000-09-12) * abstract * ---	1-8	
A	US 5 596 564 A (AZUMATANI YASUSHI ET AL) 21 January 1997 (1997-01-21) * abstract * ---	1-8	
A	EP 0 866 461 A (SONY CORP) 23 September 1998 (1998-09-23) * column 7, line 8-19 * * column 8, line 27-41 * ---	1-8	
A	EP 0 797 206 A (PIONEER ELECTRONIC CORP) 24 September 1997 (1997-09-24) * abstract * ---	1-8	TECHNICAL FIELDS SEARCHED (InCL.7)
A	WENGER, S., STOCKHAMMER, T.: "H.26L over IP and H.324 Framework" ITU STUDY GROUP 16 QUESTION 6 VIDEO CODING EXPERTS GROUP (VCEG), [Online] 21 September 2001 (2001-09-21) - 24 January 2001 (2001-01-24), pages 1-14, XP002227242 Fourteenth Meeting: Santa Barbara, CA, USA Retrieved from the Internet: <URL:http://standards.pictel.com/ftp/video -site/0109_San/VCEG-N52.doc> [retrieved on 2003-01-14] * page 1, paragraph 6 * * page 8 - page 11 * ---	1-8	H04N G11B
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 4 February 2003	Examiner Gries, T
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons A: member of the same patent family, corresponding document	

EPO FORM 1503 (03.02.02) (P4/C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 01 6412

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	SUZUKI, T. ET AL.: "Group of Pictures for JVT Codec" JOINT VIDEO TEAM (JVT) OF ISO/IEC MPEG & ITU-T VCEG, [Online] 29 January 2002 (2002-01-29) - 1 February 2002 (2002-02-01), XP002227243 2nd Meeting Geneva, CH Retrieved from the Internet: <URL:http://standards.pictel.com/ftp/video-site/0201_Gen/JVT-B069.doc> [retrieved on 2003-01-14] * the whole document *	1-8	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	WENGER, S.: "RTP payload Format for JVT Video" INTERNET ENGINEERING TASK FORCE IETF - INTERNET DRAFT, [Online] February 2002 (2002-02), XP002227245 Retrieved from the Internet: <URL:http://www.cs.columbia.edu/~hgs/rtp/drafts/draft-wenger-avt-rtp-jvt-00.txt> [retrieved on 2003-01-14] * page 3, paragraph 3.1 *	1-8	
T	STOCKHAMMER, T.: "H.26L/JVT Coding Network Abstraction Layer and IP-based Transport" IEEE INTERNATIONAL CONFERENCE ON IMAGE PROCESSING ICIP 2002, vol. II, September 2002 (2002-09), pages 485-488, XP002227244 Rochester, N.Y., US * page 486, right-hand column, paragraph 4 - page 487, right-hand column, paragraph 1; figure 2 *	1-8	
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 4 February 2003	Examiner Gries, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (01/02) (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 01 6412

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on .
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-02-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5535008	A	09-07-1996	JP 3019659 B2	13-03-2000
			JP 6268969 A	22-09-1994
			JP 2773594 B2	09-07-1998
			JP 6276485 A	30-09-1994
			JP 2947395 B2	13-09-1999
			JP 7212768 A	11-08-1995
			KR 178819 B1	01-05-1999
			US 6141491 A	31-10-2000
			US 6016382 A	18-01-2000
US 6118927	A	12-09-2000	AT 174149 T	15-12-1998
			AT 191292 T	15-04-2000
			CA 2168327 A1	31-07-1996
			CN 1134583 A	30-10-1996
			DE 69601039 D1	14-01-1999
			DE 69601039 T2	24-06-1999
			DE 69607489 D1	04-05-2000
			DE 69607489 T2	21-09-2000
			EP 0724264 A2	31-07-1996
			EP 0872839 A2	21-10-1998
			JP 2747268 B2	06-05-1998
			JP 8273304 A	18-10-1996
			JP 2857126 B2	10-02-1999
			JP 10074379 A	17-03-1998
			JP 2875237 B2	31-03-1999
			JP 10074380 A	17-03-1998
			KR 209846 B1	15-07-1999
			KR 209851 B1	15-07-1999
			KR 220529 B1	15-09-1999
			TW 434531 B	16-05-2001
			US 5870523 A	09-02-1999
US 5596564	A	21-01-1997	JP 7170492 A	04-07-1995
			US 5642338 A	24-06-1997
			US 5798995 A	25-08-1998
EP 0866461	A	23-09-1998	CN 1199906 A	25-11-1998
			EP 0866461 A2	23-09-1998
			JP 10322661 A	04-12-1998
			US 6282320 B1	28-08-2001
EP 0797206	A	24-09-1997	JP 9259541 A	03-10-1997
			DE 69715492 D1	24-10-2002
			EP 0797206 A2	24-09-1997
			US 6137954 A	24-10-2000

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82